
Application:

· Basic Application:




Limited Warranty:

IN NO EVENT THE DIRECT VENDOR'S LIABILITY EXCEED THE PRICE PAID FOR THE PRODUCT FROM DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THE PRODUCT, DIST, OR ITS DOCUMENTATION.

The direct vendor makes no warranty or representation, expressed, implied, or statutory with respect to the contents or use of this documentation, and specially disclaims its quality, performance, merchantability, or fitness for any particular purpose. The direct vendor also reserves the right to revise or update device or documentation without obligation to update. Device or documentation without obligation to update. For further inquires please contact your direct vendor.

HDMI Extender Over Cat.6



HDMI Source

HDMI Sink

Power LED

Rj45

Rj45

Introduction

The HDMI Signal Transmit unit sits next to your HDMI source.

Connect your HDMI source to the send unit. The powerful single cat.6


HDMI Extender and transmission distance of up to 50M.

Features:

- * Compact size transmitter and receiver.
- Connection between transmitter and receiver with a standard
 Network cable.
- * Works with Cat5, Cat5e, Cat6, Ethernet cable.
- * Transmission distance of up to 50M MAX (cat.6).
- * No software installation required.
- Supports high HD digital resolution up to HDTV's480p/720i/720p/ 1080i/1080p
- * Works with HDMI switch, HDMI splitter, and all kinds of HDMI/HDCP source and output Displays.
- * Housing: Metal and Aluminium

Specifications:

Model	Transmitter	Receiver
Input	HDMI connector x 1	8P8C Jack x 1
Output	8P8C Jack x 1 HDMI connector x 1	HDMI connector x 1
Bandwidth	1.65Gps	
Resolution	1920 x 1200 or 480p/720i/720p/1080i/1080p	
Operating temperature	0~45°C	
Storage temperature	-20℃~60℃	
Power Adaptor	DC 5V ,1A	
Housing	Metal and Aluminium	
Dimension(mm)	77(L) x 64(W) x 25(H)	



Input Connector

Output Connector

LED

Output Connector

Input Connector

4