


Delock 5.25" USB 3.0 Card Reader 5 slot + 4 port USB 3.0 Hub incl. V / A indicator and fan control

Description

This card reader by Delock can be installed into a 5.25" bay of a PC and will be connected to an internal USB 3.0 pin header male port. It has a 5 slot card reader and enables the connection of up to four USB devices, which the USB 3.0 hub provides. The LED display indicates the current rating and voltage values of the connected USB devices. In addition, the card reader has a slider for fan control.



Specification

- Connector:
 - external:
 - 5 x Card Reader slots
 - 4 x USB 3.0 Type-A female
 - internal:
 - 2 x USB 3.0 Type-A male
 - 1 x 4 pin power connector
 - 1 x 3 pin fan pin header male
- 1 slider for fan control
- 1 push button to select the USB port, which indicates voltage (V) and current (A)
- Chipset: GL3522 (Hub), GL3223 (Card Reader)
- Plastic housing for installation into a 5.25" bay
- Data transfer rate up to 5 Gb/s
- 4 port USB 3.0 hub supports USB Battery Charging BC 1.2 specification
- LED indicator for the card reader for power (green) and access (red)
- Cable data:
 - 2 x USB 3.0 Type-A female to 1 x 19 pin USB 3.0 pin header female
ca. 58 cm (incl. connector)
 - 1 x 4 pin power cable ca. 33 cm (incl. connector)
- Hot Swap, Plug & Play

• Supports following memory cards:

Slot 1 Compact Flash / Micro Drive	CF I, CF II, CF Extreme, CF Extreme III, CF Extreme IV, Micro Drive
Slot 2 Memory Stick	MS, High Speed Memory Stick (HS MS), MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO Duo, MS PRO Duo Mark2, MS PRO-HG, MS PRO-HG Duo, MS PRO-HG Duo HX, MS Micro*, MS PRO Micro*, MS-HG Micro*, MS XC-HG Micro*, M2*
Slot 3 xD	xD, xD type M, xD type H
Slot 4 Micro SD	microSD, Micro SDHC, Micro SDHC Ultra, T-Flash

Item No. 91494

EAN: 4043619914944

Country of origin: China

Package: Retail Box



Slot 5 Secure Digital / Multi Media Card	SD, SD Ultra, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, SDXC Ultra, MMC, miniSD, MMCmobile, RS- MMC
---	---

*Adapter is required



System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.7
- PC with one free 5.25" bay
- Mainboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin power connector
- Fan with a free 3 pin fan control connection cable

Package content

- 5.25" Card Reader
- 2 x cable
- Screws
- User manual

Images



General	
Form factor:	5.25"
Funktion:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.7 Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
LED indicator:	V / A indicator for hub
Interface	
External:	1 x CF slot 1 x MS slot 1 x Micro SD slot 1 x SD slot 1 x xD slot 4 x USB 3.0 Type-A female
Internal:	2 x USB 3.0 Type-A male 1 x 4 pin power connector 1 x 3 pin fan pin header male
Technical characteristics	
Chipset:	Genesys Logic
Data transfer rate:	USB 3.1 Gen 2 up to 10 Gb/s
Physical characteristics	
Colour:	black