



Delock 3.5" USB 3.0 Card Reader 5 slot + 4 port USB 3.0 Hub

Description

This card reader by Delock can be installed into a 3.5" bay of a PC and will be connected to an internal USB 3.0 pin header male port. It has a 5 slot card reader and enables the connection of up to four USB devices, which the USB 3.0 hub provides.



Specification

Connector:

external:

5 x Card Reader slots

4 x USB 3.0 Type-A female

internal:

1 x 19 pin USB 3.0 pin header female

- 1 x 4 pin power connector
- · Chipset: GL3522 (Hub), GL3223 (Card Reader)
- Metal housing for installation into a 3.5" bay
- Data transfer rate up to 5 Gb/s
- 4 port USB 3.0 hub supports USB Battery Charging BC 1.2 specification
- LED indicator for the card reader for power (green) and access (red)
- · Cable data:
- 1 x 19 pin USB 3.0 pin header female cable ca. 53 cm (incl. connector)
- 1 x 4 pin power cable ca. 29 cm (incl. connector)
- · Hot Swap, Plug & Play

• Supports following memory cards:

Slot 1 Compact Flash / Micro Drive	CF I, CF II, CF Extreme, CF Extreme III, CF Extreme IV, Micro Drive
Slot 2 Memory Stick	MS, High Speed Memory Stick (HS MS), MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO Duo, MS PRO Duo Mark2, MS PRO-HG, MS PRO-HG Duo, MS PRO-HG Duo HX, MS Micro*, MS PRO Micro*, MS-HG Micro*, MS XC-HG Micro*, M2*
Slot 3 xD	xD, xD type M, xD type H
Slot 4 Micro SD	microSD, Micro SDHC, Micro SDHC Ultra, T-Flash
Slot 5 Secure Digital / Multi Media Card	SD, SD Ultra, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, SDXC Ultra, MMC, miniSD, MMCmobile, RS- MMC

^{*}Adapter is required

Item No. 91493

EAN: 4043619914937

Country of origin: China

Package: Retail Box







System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.7
- PC with one free 3.5" bay
- Mainboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin power connector

Package content

- 3.5" card reader with connection cable
- Screws
- User manual

Images











General	
Form factor:	3.5"
Funktion:	Hot Swap
	Plug & Play
Supported operating system:	Linux Kernel 3.7
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
Interface	
External:	1 x CF slot
	1 x MS slot
	1 x Micro SD slot
	1 x SD slot
	1 x xD slot
	4 x USB 3.0 Type-A female
Internal:	1 x 4 pin power connector
	1 x 19 pin USB 3.0 pin header female
Technical characteristics	
Chipset:	Genesys Logic
Data transfer rate:	USB 3.1 Gen 2 up to 10 Gb/s
Physical characteristics	
Colour:	black