DGD2404















TRIBRID 4CH REAL-TIME HD CCTV DVR

FEATURES

Free P2P Cloud EaZy Networking*

- Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- The "Buddy" feature to share the device access permission to other people.
- Device login / out notifications reported.



Video Backup


Regular backup could be configured to automatically copy video footages to the specified location (USB drive or FTP) at the specified time.

Remote Surveillance

- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- CMS Lite for 24 devices central management
- Applicable also to Apple's media player, QuickTime.

Tribrid Video Input

- Supports Analog HD / TVI / 960H video input.
- All channels at 1080P real-time recording




Push Status -

Active Event Notification with EagleEyes App

Push Status to send instant notifications for system events, such as video loss or HDD data removal.



REAR PANEL



SPECIFICATIONS

▼ Video				
Video System		NTSC / PAL (auto detection)		
Video Compression Format		H.264		
Video Signal		Analog HD / TVI / 960H		
Video Input		4 channels(Composite video signal 1 Vp-p 75Ω BNC)		
Video Output	BNC	YES		
vidoo Odiput	VGA	YES		
	HDMI	YES		
Video Resolution		1080P / 720P / QHD / 960H / Frame / Field / CIF		
▼ Record & Backu	D			
Max. Recording Rate		Up to 120 IPS @ 1920 x 1080		
Recording Mode		Manual / Timer / Motion / Remote		
Pre-alarm Recording		YES		
Playback Channel		4CH		
Quick Search		Time / Motion search mode		
Backup Device		USB 2.0 drive / Network		
Regular Backup		YES		
▼ Audio				
Audio Input		1 audio input		
Audio Output		1 audio output (Mono)		
▼ General				
Hard Disk Storage		6TB SATA HDD x 2		
SATA Interface		YES		
Image Quality Setting		SUPER BEST / BEST / HIGH / NORMAL		
USB Mouse Control		YES		
Motion Detection Area		16 × 12 grids per channel		
Motion Detection Sensitivity		3 adjustable parameters for accurate detection		
Event Notification		Push Status / FTP / E-Mail		
Picture Zoom		2X digital zoom		
PTZ Control		YES		
RS485		YES		
IR Remote Control		YES (IR receiver built-in)		
Key Lock (Password Protection)		YES		
User Level		4 user levels for different access privilege		
Video Loss Detection		YES		
Camera Title		Supports up to 25 letters		
Video Adjustable		Hue / Saturation / Contrast / Brightness		
Date Display Format		YY/MM/DD, DD/MM/YY & MM/DD/YY		
Daylight Saving		YES		
Power Source (±10%)		DC12V / 3A		
Operating Temperature		10°C ~ 40°C (50°F ~104°F)		
Operating Humidity		10% ~ 85%		
Dimensions (mm)**		345(W) × 58.8(H) × 223(D)		



SPECIFICATIONS

▼ Network				
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet			
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS			
▼ Remote Surveillance from PC				
Compatible Operating System	Windows & MAC			
Compatible Program	Web Browser:	Internet Explorer, Google Chrome & Safari		
	CMS Lite:	24CH central management software for Windows OS		
	QuickTime:	For both Windows and MAC operating systems		
Max. online users	20			
Web Transmitting Compression Format	H.264			
Network Live Audio	YES			
Remote Independent Operation	YES			
Remote Event Download & Playback	YES			
▼ Mobile Surveillance				
Арр	EagleEyes			
Compatible Devices	iOS & Android devices			
Push Status	YES			
▼ Others				
EaZy Networking	YES			
DCCS Support	YES			
AVTECH Free DDNS service	YES			
Privacy Mask	YES			
Multiplex Operation	Live display / record / playback / backup / network operations			
System Recovery	System auto recovery after power failure			
Optional Peripherals	HDMI Matrix (HDM02) / USB Joystick (AVX102)			

^{*} The specifications are subject to change without notice.

** Dimensional tolerance: ±5mm