



## DisplayPort to 2-Port DisplayPort Splitter Hub with MST

4K@30Hz, USB Power, Video Wall Function

Part No.: **207768**

---

Easily distribute a single Ultra-High-Definition (UHD) signal to multiple displays. The Manhattan DisplayPort to 2-Port DisplayPort Splitter Hub with Multi-Stream Transport (MST) streams a 4K DisplayPort (DP) signal from a single UHD source to up to two UHD displays.

### Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, video conferencing, presentations and retail applications, the Manhattan DisplayPort to 2-Port DisplayPort Splitter Hub with MST features a built-in booster for added signal strength. It's a great choice for splitting and distributing a synchronous signal, in either mirrored or extended modes, to multiple 4K DP displays. MST mode creates a video wall from two displays giving the user a more immersive experience while gaming, in a conference setting or in a home office.

### Quality Construction and Easy Installation

Full compliance with DisplayPort, HDCP 2.2 and DVI 1.0 ensures that the Manhattan DisplayPort to 2-Port DisplayPort Splitter Hub with MST can provide long service and reliable performance. Quickly connect DP cables (not included) and the included USB power cable, and this affordable, Ultra-High-Definition 4K DisplayPort solution is complete — no software/hardware configuration or complicated settings required.

### Features:

- Duplicates an Ultra-High-Definition (UHD) DisplayPort signal for up to two UHD DisplayPort displays
- 4K@30Hz resolution, full 3D video and Deep Color
- Supports compressed DTS Master Audio, as well as 7.1 surround sound audio up to 192 kHz
- Supports Mirror, Extended and Mutli-Stream Transport (MST) modes to maximize work or gaming capabilities
- Mirror mode duplicates the computer screen onto two displays with resolutions up to 4K@30Hz
- Extended mode expands the desktop workspace to up to two additional screens with resolutions up to 4K@30Hz

- Multi-Stream Transport (MST) mode creates a video wall for a more immersive experience, using two screens — with resolutions up to 3840x2160 at 30Hz — as one
- USB powered with Plug and Play installation; no special setup or remote required
- Integrated DisplayPort cable
- Ideal for enhancing display capabilities or creating a video wall in schools, churches, conference rooms, trade shows and retail outlets; perfect for digital signage and AMD Eyefinity Technology in gaming
- HDCP 2.2 compliant
- Gold-plated contacts for corrosion-free connections
- Three-Year Warranty

## Specifications:

### Standards and Certifications

- DP 1.2
- HDCP 2.2
- DVI 1.0
- CTS 1.4a
- CE
- FCC
- RoHS2

### Connections

- One DisplayPort (DP) male (input)
- Two DisplayPort (DP) female (output)
- One 5 V / 2 A USB Micro-B power female (input)

### Signal Input/Output

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 5.4 Gbps, 3840x2160 at 30 Hz resolution
- Output video: HDCP 2.2, DVI 1.0

### Video Resolutions

- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz

### Physical

- Dimensions: 255 x 50 x 11 mm (9.8 x 2.0 x 0.4 in.)
- 5 V / 1 A USB Micro-B power cable: 1 m (3 ft.)
- Weight: 50 g (1.8 oz.)
- Housing: plastic

### Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

#### System Requirements

- Windows XP/Vista/7/8.1/10
- DP 1.2 graphics card for MST function

#### Package Contents

- DisplayPort to 2-Port DisplayPort Splitter Hub with MST
- USB power cable
- Quick Instruction Guide

