



DisplayPort 1.2a to DVI-D Adapter

DisplayPort 1.2a Male to DVI-D Female, Active, 23 cm (9 in.), Black

Part No.: [152228](#)

Easily connect a DisplayPort source to an DVI-D display.

The Manhattan DisplayPort Adapter helps establish a fast, simple and convenient link between newer DisplayPort-equipped sources and existing DVI-D displays. The Manhattan DisplayPort Adapter is easy and quick to install. No complicated configuration or setup is required, which helps fully realize the investment, value and service life of DVI-D displays. Its all-in-one design is a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features:

- Actively converts a DisplayPort signal to a DVI-D dual-link signal
- Delivers a high-quality digital video signal – ideal for using a new DisplayPort source with an existing DVI-D display
- Supports Deep Color, high-bandwidth 10.8 Gbps applications and resolutions up to 1920x1080@60Hz
- Integrated cable design relieves port pressure; built-in screw holes secure cable connection
- Compatible with surround and multidisplay modes, nVidia® and AMD® Eyefinity, and with D++ (dual mode graphics cards)
- Three-Year Warranty

Specifications:

Standards and certifications

- Displayport 1.2a
- HDCP

General

- 8-bit and 10-bit Deep Color support
- 10.8 Gbps bandwidth
- Auxiliary channel support, 1 Mbps
- One-lane, one-direction, four-line connection support
- Active

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Connectors

- DisplayPort 20-pin male
- DVI-D 24+1-pin female
- Gold-plated contacts
- ABS boots, built-in PVC strain relief

Physical

- Length: 23 x 4 x 1.5 cm (9 x 1.7 x 0.6 in.)
- Weight: 4 g (0.9 oz.)

Operating Environment

- Operation Temperature: 0 - 50°C (32 - 122°F)
- Storage Temperature: -10 - 80°C (14 - 176°F)
- Humidity (noncondensing): 0 - 96%

Package contents

- DisplayPort 1.2a to DVI-D Adapter

