



4K 2-Port HDMI Splitter

4K@60Hz, AC Powered, HDCP 2.2, Black

Part No.: **207591**

Easily distribute a single Ultra-High-Definition (UHD) signal to multiple displays. The Manhattan 2-Port HDMI Splitter streams a 4K HDMI signal from a single UHD source to up to two UHD displays.

Flexible Solution for Many A/V Applications

Ideal for trade shows, classrooms, video conferencing, presentations and retail applications, the Manhattan 4K 2-Port HDMI Splitter features a built-in booster for added signal strength. It's a great choice for splitting and distributing a synchronous signal to multiple 4K HDMI displays when source equipment is remotely stored in a secured room or cabinet. Cascade multiple units up to three levels to output HDMI video/audio to additional displays in widely distributed applications.

Quality Construction and Easy Installation

Full compliance with HDMI, HDCP 2.2 and DVI 1.0 ensures that the Manhattan 4K 2-Port HDMI Splitter can provide long service and reliable performance. Quickly connect HDMI cables (not included) and the 5 V / 1 A power adapter without software/hardware configuration or complicated settings to complete this affordable Ultra-High-Definition, 4K HDMI solution.

Features:

- Duplicates an Ultra-High-Definition (UHD) digital audio/video signal for up to two UHD HDMI displays
- 4K@60Hz resolution, full 3D video and Deep Color
- Supports video amplifier bandwidth up to 300 MHz, 3 Gbps per channel (10.2 Gbps total) for 4Kx2K displays
- Supports compressed DTS-HD Master Audio, uncompressed LPCM 8 channel (7.1 surround sound) audio and Dolby TrueHD as well as 32-channel audio
- Supports 48-bit Deep Color (12-bits per channel), xvYCC (x.vColor), Rec. 2020 color space and 21:9 aspect ratio
- Supports LPCM, DTS Digital, DTS-HD Master Audio, Dolby TrueHD audio, four audio streams and 32-channel audio
- HDCP 2.2 compliant
- AC powered with Plug and Play installation; no special setup or remote required

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Rugged metal housing for maximum durability; built-in wall-mounting holes
- Up to three splitters may be cascaded to support four 4K displays
- Gold-plated contacts for corrosion-free connections
- Works with PlayStation and Xbox game systems, Blu-ray players, set-top boxes, satellite receivers and more
- Three-year warranty

Specifications:

Standards and Certifications

- HDCP 2.2
- DVI 1.0
- CTS 1.4a
- CE
- FCC
- RoHS2

Connections

- One HDMI female (input)
- Two HDMI female (output)
- One 5 V / 1 A DC power female (input)

Signal Input/Output

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 10.2 Gbps, 4096x2160 at 60 Hz resolution
- Output video: HDCP 2.2, DVI 1.0

Video Resolutions

- VGA: 640x480, 800x600, 1024x768, 1920x1200
- DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@60Hz

Physical

- LED indicators: power and port connection
- Dimensions: 80 x 80 x 20 mm (3.2 x 3.2 x 0.8 in.)
- 5 V / 1 A power adapter: 1.2 m (3.9 ft.)
- Weight: 150 g (5.3 oz.)
- Housing: metal
- Two wall-mount holes

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 - 96%

Package Contents

- 4K 2-Port HDMI Splitter

- 5 V / 1 A power adapter
- Quick Instruction Guide

