

NEW PRODUCTS

Televés

UHF Antenna DAT 75

Ref. 1097

Televés launches its new UHF antenna, the DAT 75.

It has two clamps, a reflector, a dipole, an antenna box, an especially designed impedance adaptor circuit, an F connector and a sleeve to protect it from the rain.

■ Clamps: The system now has two clamps so that the antenna is more firmly fixed to the mast, making the installation more secure.

■ Reflector: We have improved the way that the reflector is fixed to the rest of the antenna so that it is more robust and easier to install.

■ Antenna box: This is shielded, so that it provides greater protection against the impulsive noise. It also comes with an especially designed impedance adaptor circuit.

■ Output F connector: The antenna box features an output F connector, as well as a sleeve that protects it from the rain.

■ This antenna also features a new series of plastic pieces used to support the dipole and the structure in general with a new attractive appearance.

■ The DAT75 antenna can also be used with our MRD (Margin Rising Device), ref. 5050, which eliminates the impulsive noise, and improves the technical specifications.



| | | |
|-----------------------|-----|--------------------------------|
| Bandwidth (frequency) | MHz | Channels 21 - 69 (470 - 862) |
| Gain | dB | 19 |
| Front-to-back ratio | dB | 28 |
| Hor. opening angle | ° | 27 |
| Vert. opening angle | ° | 32 |
| Polarisation | | Horizontal / Vertical (lineal) |
| Length | mm | 1.825 |
| Number of elements | | 75 |